



This product available in **biodegradable alternatives**.



MEGA FORTRIS GROUP

Indicative Seal · Data Sheet

Fast Seal SP CWPP (FSSP)



Versatile Pull-tight Seal with Metal Locking

A flexible pull-tight seal, the Fast Seal SP features a metal locking mechanism that provides higher security and sealing capabilities.

The Fast Seal SP is user-friendly and easy to apply and remove for small sealing facilities e.g. cassettes for ATM machines and money boxes on which it is widely utilised. The heat staking technology used in manufacturing the Fast Seal SP ensures the seal is also highly tamper-evident.

Indicative Flat Stem Pull Tight Seal

Features

- 1 The Fast Seal SP is etched with permanent laser marking. Laser marking offers the highest level of security as it cannot be removed and replaced.
- 2 Heat staking technology is used to permanently fix the cap to the Fast Seal SP. Heat staked parts are bonded too strongly to be cut or forced open without leaving clear evidence of tampering.
- 3 Metal clip locking provides greater pull strength to the thin and flexible strap.
- 4 Colour coding is made possible by using combinations of white-based seals and multi-coloured caps. A floating metal clip is shielded securely by a cap, providing great locking strength and security.
- 5 Optional- **Biodegradable** additive can be added upon customers' requirement, securing strap gives the user a choice of strength to match different applications.

Technical Specifications

PRODUCT - FAST SEAL SP 5/8/12 (FSSP)

Product	Material	Locking Space	Strap Dimensions	Pull Strength	Marking Area	Max Marking Digits
FS SP 5"	Body: PP / Nylon & Biodegradable	125 mm	∅ 2.30 mm	18 kg (PP)	Flap: 45 x 15 mm	14
FS SP 8"		200 mm		21 kg (NY)		
FS SP 12"		300 mm				

PACKAGING

Carton	Quantity	Dimensions (mm)	Gross Weight kg	Volume m ³	Standard Colours
Inner Carton					
FS SP 5"	1,000	279 x 214 x 160 mm	3.06	0.00955	Body RED BLUE ORANGE YELLOW GREEN WHITE Cap WHITE
FS SP 8"	1,000	354 x 214 x 156 mm	3.50	0.01182	
FS SP 12"	1,000	450 x 210 x 215 mm	3.80	0.02032	
Outer Carton					
FS SP 5"	5,000	815 x 285 x 225 mm	15.30	0.05226	
FS SP 8"	5,000	800 x 360 x 225 mm	17.50	0.06480	
FS SP 12"	5,000	1070 x 458 x 225 mm	19.00	0.11026	



FMM EXCELLENCE AWARD 2012
QUEST FOR CONTINUOUS IMPROVEMENT
BEST MANUFACTURER IN MALAYSIA IN 2012

UPDATED : 28 JULY 2020